



IFZA Business Park, Dubai Silicon Oasis

Forumchem Technical Specification Sheet

Snow White Petroleum Jelly Batch No. CCTRDWPJ19180393 Packing: Drums

| TEST | METHOD | Unit | SPECIFICATION |
|----------------------------------|--------------------|-------|------------------|
| Appearance | Visual | | Clear White |
| Specific Gravity @60 °C | USP | gm/ml | 0.810-0.870 |
| Drop Melting Point | ASTM D-127 | °C | 50 to 60 °C |
| Melting Point (CAPILLARY) | USP 31 | °C | 45-55 |
| Acidity or Alkalinity | B.P. 2012 | рН | According method |
| Polycyclic Aromatic Hydrocarbons | B.P. 2012 | | Passed |
| Odor | On rubbed the skin | | Odorless |
| Sulphated ash | B.P. 2012 | % | Less than 0.05% |
| Kinematic viscosity @100°C | ASTM D-445 | cSt. | 5 to 8.0 cSt |
| Cone Penetration @25 °C | ASTM D-937 | dmm | 120 to 165 |
| Congealing point | ASTM D-938 | °C | 50 to 60 °C |
| Flash point | ASTM D-92 | °C | Min. 210 |

Product results are reported by an Independent Third-Party Surveyor.

Re testing is recommended every 12 months from original testing date to verify product quality.